




LTB-1F翻边衬套标准公制尺寸 Flanged Bearing Standard Metric Size



S_3	1.0	1.5	2.0	2.5
r	$1^{-0.5}$	1 ± 0.5	1.5 ± 0.5	2 ± 0.5

单位unit:mm

轴径 D_s	6 -0.013 -0.028	8 -0.013 -0.028	10 -0.016 -0.034	12 -0.016 -0.034	14 -0.016 -0.034	15 -0.016 -0.034	16 -0.016 -0.034
座孔 H7 D_H	8 $+0.015$	10 $+0.015$	12 $+0.018$	14 $+0.018$	16 $+0.018$	17 $+0.018$	18 $+0.018$
外径公差 D_o	8 $+0.055$ $+0.025$	10 $+0.055$ $+0.025$	12 $+0.055$ $+0.025$	14 $+0.065$ $+0.030$	16 $+0.065$ $+0.030$	17 $+0.065$ $+0.030$	18 $+0.065$ $+0.030$
装配后内孔公差 $D_{i,a}$	6.055 5.990	8.055 7.990	10.058 9.990	12.058 11.990	14.058 13.990	15.058 14.990	16.058 15.990
间隙 C_D	0.077 0.000	0.083 0.003	0.086 0.003	0.092 0.006			
法兰尺寸 D_{fi}	12	15	18	20	22	23	24
法兰壁厚 S_{fi}	0 -0.2						

轴径 D_s	18 -0.016 -0.034	20 -0.020 -0.041	22 -0.020 -0.041	25 -0.020 -0.041	30 -0.025 -0.050	35 -0.025 -0.050	40 -0.025 -0.050
座孔 H7 D_H	20 $+0.021$	23 $+0.021$	25 $+0.021$	28 $+0.021$	34 $+0.025$	39 $+0.025$	44 $+0.025$
外径公差 D_o	20 $+0.075$ $+0.035$	23 $+0.075$ $+0.035$	25 $+0.075$ $+0.035$	28 $+0.075$ $+0.035$	34 $+0.075$ $+0.035$	39 $+0.085$ $+0.045$	44 $+0.085$ $+0.045$
装配后内孔公差 $D_{i,a}$	18.061 17.990	20.071 19.990	22.071 21.990	25.071 24.990	30.085 29.990	35.085 34.990	40.085 39.990
间隙 C_D	0.095 0.006	0.112 0.010			0.126 0.010	0.135 0.015	
法兰尺寸 D_{fi}	26	30	32	35	42	47	53
法兰壁厚 S_{fi}	0 -0.2	0 -0.2			0 -0.2		

注：长度B按客户需求制作